



PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In the Application of:

Applicant : John M. Hetzel, Jr.  
 Serial No. : 09/689,131  
 Title: FIBERGLASS COMPOSITE FIRE FIGHTING HELMET AND  
 METHOD FOR MAKING A FIBERGLASS COMPOSITE  
 FIREFIGHTING HELMET  
 Docket : 520219-273  
 Examiner : S. Staicovici  
 Art Unit : 1732

Assistant Commissioner for Patents  
 Washington, D.C. 20231

DECLARATION UNDER 37 C.F.R. §1.132

I, Teresa A. Lawson, do declare and state that:

1. I am Helmet Production Manager of Lion Apparel, Inc., the assignee of the above-identified patent application. I have reviewed and am familiar with the above-identified patent application.

2. I have served as Helmet Production Manager at Lion Apparel, Inc. for approximately three years, and have a total of 13 years of practical engineering experience. I graduated from ITT Technical Institute in 1994 with a two-year degree in Tool Design.

3. In November 2002 Ashland Specialty Chemical Co., at the request of Lion Apparel, Inc., conducted tests upon a helmet formed using the steps recited in the claims of this application, wherein such a helmet includes ceramic particles (termed the "Ceramic Helmet" herein). These tests compared the performance of the Ceramic Helmet to a helmet of similar size, shape, materials and dimensions, but which lacked any ceramic particles (termed the "Control Sample" herein). Attachment A includes a series of tables including the results of such testing.

4. Pages 1 and 2 of Attachment A provide test results relating to the tensile strength of the Control Sample (page 1) and the Ceramic Helmet (page 2). As can be seen in pages 1 and 2,

Serial No. 09/689,131  
Attorney Docket No.: 520219-273  
Declaration

testing shows that the mean maximum tensile strength of the Ceramic Helmet is 15,483 psi, and the mean tensile strength of the Control Sample is 10,477 psi. Thus, the Ceramic Helmet showed a 48% increase in maximum tensile strength over the Control Sample.

5. Pages 3 and 4 of Attachment A provide test results relating to the flexural strength of the Control Sample (page 3) and the Ceramic Helmet (page 4). As can be seen at pages 3 and 4, testing shows that the mean flexural strength of the Ceramic Helmet is 28,183 psi, and the mean tensile strength of the Control Sample is 21,158 psi. Thus, the Ceramic Helmet showed a 33% increase in flexural strength over the Control Sample.

6 Pages 5-8 of Attachment A provide data relating to a drop dart evaluation for determining impact resistance of the Ceramic Helmet and the Control Sample. The drop dart test involves dropping a dart of predetermined size, shape and weight from various heights to determine at what drop height the dart causes the helmet to fail or rupture. As can be seen at pages 6 and 8 of Attachment A, the mean height from which the dart is dropped and causes failure of the Ceramic Helmet is 9.5 inches, as compared to 9 inches for the Control Sample. Thus, the Ceramic Helmet showed a 6% increase in impact resistance over the Control Sample as measured by the drop dart evaluation method.

7. Pages 9 and 10 of Attachment A provide test data relating to the izod impact test. The izod impact test involves swinging an arm of a predetermined size and shape into a test sample with a uniform force. The transmitted force of the impact is then measured. The izod test was carried out on notched sample (i.e. a sample with a notch or cut-out formed therein) as well as an unnotched sample. As can be seen at pages 9 and 10 of Attachment A, testing shows that the mean impact resistance of the notched Ceramic Helmet is 8.15 ft-lbs/in, and the mean impact resistance of the notched Control Sample is 7.9 ft-lbs/in. Thus, the Ceramic Helmet showed a 3% increase in impact resistance over the Control Sample as measured by the izod impact test for a notched sample.

8. Pages 9 and 10 of Attachment A shows that the mean impact resistance of the unnotched Ceramic Helmet is 14.25 ft-lbs/in, and the mean impact resistance of the unnotched Control Sample is 14.81 ft-lbs/in. Thus, the Ceramic Helmet showed a 3% decrease in impact

Serial No. 09/689,131  
Attorney Docket No.: 520219-273  
Declaration

resistance over the Control Sample as measured by the izod impact test for an unnotched sample.

9. As shown at page 11 of Attachment A, the percentage of glass and the percentage of ash differed by 1% between the Control Sample and the Ceramic Helmet. However, in my opinion this small change in percentage would have only a minor effect upon the testing results, and in my opinion the presence of the ceramic particles is the main reason for the difference in performance between the Control Sample and the Ceramic Helmet.

10. Lion Apparel, Inc., the assignee of the above-identified patent application, markets, manufactures and sells the Ceramic Helmet under the trademark AMERICAN CLASSIC™. Attachment B shows the sales history of the Ceramic Helmet, and also includes sales data for other helmets sold by Lion Apparel, Inc. Lion Apparel currently markets, manufactures and sells five other types of helmets besides the AMERICAN CLASSIC.

11. As can be seen at the bottom of page 1 of Attachment B, for the period of December 2001-November 2002, Lion Apparel sold 7,332 Ceramic Helmets, which represented 28% of all helmets sold by Lion Apparel during that period.

12. As can be seen at the bottom of page 1 of Attachment B, for the period of December 2002-November 2003, Lion Apparel sold 9,727 Ceramic Helmets, which represented 40% of all helmets sold by Lion Apparel during that period.

13. As can be seen at the bottom of page 1 of Attachment B, for the period of December 2003-November 2004, Lion Apparel sold 7,954 Ceramic Helmets, which represented 38% of all helmets sold by Lion Apparel during that period.

14. As can be seen at page 1 of Attachment B, for the period of December 2001-November 2004, Lion Apparel has sold 25,013 Ceramic Helmets.

15. As can be seen in page 2 of Attachment B, for the period of March 2003-February 2004 Lion Apparel sold 8,535 Ceramic Helmets, and for the period of March 2004-February 2005 Lion Apparel sold 9,641 Ceramic Helmets.

16. For the period of March 2003-February 2005 Lion Apparel sold 18,994 of the Ceramic Helmets, making it the most popular helmet sold by Lion Apparel during that time period.


Serial No. 09/689,131  
Attorney Docket No.: 520219-273  
Declaration

17. The Ceramic Helmet, and other helmets sold by Lion Apparel, are advertised in similar manners and have similar advertising budgets. In fact, all helmets sold by Lion Apparel are typically marketed in print in the same brochures and literature.

18. In my opinion the fact that the Ceramic Helmet is formed using the steps recited in the claims of this application, wherein such a helmet includes ceramic particles is a direct cause of the commercial success of the Ceramic Helmet.

19. Attachment C is a print out from Lion Apparel's web page [www.lionapparel.com](http://www.lionapparel.com), and more particularly [www.paulconwayhelmets.biz/Classic.html](http://www.paulconwayhelmets.biz/Classic.html), featuring the ceramic features of the Ceramic Helmet.

I hereby declare that all statements herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

  
Teresa A. Lawson


Date: April 6, 2005

368003

Dec 22 2004 12:15PM

LION APPAREL

No 5146 P 2



ASHLAND SPECIALTY CHEMICAL CO  
PHYSICAL TESTING LAB  
INSTRON 4204

TENSILE TEST - ENCL 17  
ASTM D-638 (MAT-2202)

Test type: Tensile  
Operator name: SLH  
Sample Identification: 50989T1  
Interface Type: 4200

Instron Corporation  
Series IX Automated Materials Testing System 8 06.00  
Test Date: Wednesday, November 27, 2002

Sample Rate (pts/secs): 5.0000  
Crosshead Speed: 0.2000 in/min  
2nd Crosshead Speed: 0.0000 in/min  
Full Scale Load Range: 10000.000 lbf

Humidity (%) : 50  
Temperature: 71 F

SAMPLE ID: FR 998/35 Control

WNLIMS ID:

Sample comments:

	Maximum Tensile Strength (psi)	Modulus (ksi)	Elongation at Max Load (%)	Stress at Yield (psi)	Elongation at Yield (%)	Elongation at Break (%)	Width (in)	Thickness (in)
1	10459	1177.2	1.15	-	-	1.15	0.506	0.105
2	10562	1077.6	1.43	-	-	1.43	0.505	0.107
3	8729	1354.3	0.82	-	-	0.83	0.501	0.120
4	12366	1240.2	1.37	-	-	1.37	0.501	0.104
5	10272	1176.3	1.01	-	-	1.02	0.503	0.114
Mean	10477	1205.1	1.16			1.16	0.503	0.110
S.D.	1291	101.7	0.25			0.25	0.002	0.007

Reviewed By KVM

Reviewed Date 11/27/02

ASHLAND SPECIALTY CHEMICAL CO  
PHYSICAL TESTING LAB  
4444 INSTRONFLEX TEST - ENGLISH UNITS  
ASTM D-790 (MAT-2203)Test type: Flex  
Operator name: SLH  
Sample Identification: 50989F1  
Interface Type: 4200Instron Corporation  
Series IX Automated Materials Testing System 8 03 10  
Test Date: Wednesday, November 27, 2002Sample Rate (pts/sec): 2.0000  
Crosshead Speed: 0.0500 in/min  
2nd Crosshead Speed: 0.0000 in/min  
Full Scale Load Range: 400.000 lbfHumidity ( % ): 50  
Temperature: 71 F

SAMPLE ID: FR 998/35 Control

WINLIMS ID:

## Sample comments:

	Flexural Strength (psi)	TANGENT MODULUS (ksi)	Load at Yield (lbs)	Strain at Yield (in/in)	Width (in)	Thickness (in)	Span (in)	Toughness (psi)
1	22222	1012.5	97.2	0.027	0.992	0.115	2.000	44.504
2	18974	939.1	81.3	0.026	0.989	0.114	2.000	36.197
3	19155	963.3	81.6	0.025	1.001	0.113	2.000	37.162
4	20434	988.4	88.4	0.024	0.999	0.114	2.000	32.085
5	25005	1150.2	79.9	0.027	0.998	0.098	2.000	45.675
Mean	21158	1010.7	85.7	0.026	0.996	0.111	2.000	39.125
S.D.	2512	82.7	7.2	0.001	0.005	0.007	0.000	5.784

ASHLAND SPECIALTY CHEMICAL CO  
PHYSICAL TESTING LAB  
INSTRON 4204

TENSILE TEST - ENGLISH UNITS  
ASTM D-638 (MAT-2202)

Test type: Tensile  
Operator name: SLH  
Sample Identification: 50989T2  
Interface Type: 4200

Instron Corporation  
Series IX Automated Materials Testing System 8 06 00  
Test Date: Wednesday, November 27, 2002

Sample Rate (pts/secs): 5.0000  
Crosshead Speed: 0.2000 in/min  
2nd Crosshead Speed: 0.0000 in/min  
Full Scale Load Range: 10000 000 lbf

Humidity ( % ): 50  
Temperature: 71 F

SAMPLE ID: FR 998/35 Ceramic

WTNLTMS ID:

Sample comments:

	Maximum Tensile Strength (psi)	Modulus (ksi)	Elongation at Max Load (%)	Stress at Yield (psi)	Elongation at Yield (%)	Elongation at Break (%)	Width (in)	Thickness (in)
1	14676	1321.5	1.34	-	-	1.35	0.508	0.119
2	15093	1445.9	1.33	-	-	1.33	0.507	0.113
3	19820	1590.8	1.66	19636	1.62	1.66	0.505	0.098
4	14999	1354.6	1.33	-	-	1.33	0.501	0.105
5	12826	1332.3	1.13	-	-	1.13	0.501	0.108
Mean	15483	1409.0	1.36	0	0.00	1.36	0.504	0.109
S.D.	2594	112.8	0.19	0	0.00	0.19	0.003	0.008

ASHLAND SPECIALTY CHEMICAL CO  
PHYSICAL TESTING LAB  
4444 INSTRONFLEX TEST - ENGLISH UNITS  
ASTM D-790 (MAT-2203)Test type: Flex  
Operator name: SLH  
Sample Identification: 50989F2  
Interface Type: 4200Instron Corporation  
Series IX Automated Materials Testing System 8.03.10  
Test Date: Wednesday, November 27, 2002Sample Rate (pts/secs): 2.0000  
Crosshead Speed: 0.0500 in/min  
2nd Crosshead Speed: 0.0000 in/min  
Full Scale Load Range: 400.000 lbfHumidity (%): 50  
Temperature: 71 F

SAMPLE ID: FR 998/35 Ceramic

WINLIMS ID:

## Sample comments:

	Flexural Strength (psi)	TANGENT MODULUS (ksi)	Load at Yield (lbs)	Strain at Yield (in/in)	Width (in)	Thickness (in)	Span (in)	Toughness (psi)
1	28949	1032.4	183.4	0.031	0.998	0.138	2.000	59.656
2	24212	1022.4	128.0	0.025	0.999	0.126	2.000	43.484
3	32589	1219.5	149.3	0.028	1.004	0.117	2.000	57.222
4	26715	1102.4	125.6	0.028	0.996	0.119	2.000	51.798
5	28448	1095.4	141.0	0.027	0.999	0.122	2.000	49.899
Mean	28183	1094.4	145.5	0.028	0.999	0.124	2.000	52.412
S.D.	3082	78.6	23.3	0.002	0.003	0.008	0.000	6.364



**ASHLAND SPECIALTY CHEMICAL CO.**  
**PHYSICAL TESTING LAB**  
**ASTM D-5420-98a**

## DROP DART EVALUATION AND CALCULATIONS

AF NUMBER:	50989
REQUESTER:	Fowler
DATE:	11/27/2002
ANALYST:	SLH

**SAMPLE ID: FR 998/35 Control**

GEOMETRY USED FOR THIS TEST (A,B,or C):  
 DROP WEIGHT USED FOR THIS TEST (lbs):  
 INCREMENT OF HEIGHT(dh) TO BE EMPLOYED:  
 NUMBER OF SPECIMENS TO BE TESTED:

A	
0.5	lbs
1	inches
15	.

GEOM.	(MAT-2229)	TUP DIA.	SUPPORT RING

A	625+004	3.00+0.01
B	625+004	1.25+0.01
C	625+004	0.84+0.01

Use "X" for failure. Use "O" for non-failure

[illegible]

Thickness (inches)
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20

**AVERAGE:**

Q:\XLD\OCSMATERIAL\DROPDART.XLS  
REVISION DATE: 5-1-2000



**ASHLAND SPECIALTY CHEMICAL CO.**  
**PHYSICAL TESTING LAB**  
**ASTM D-5420-98a**

## DROP DART EVALUATION AND CALCULATIONS

AF NUMBER:	50989
REQUESTER:	Fowler
DATE:	11/27/2002
ANALYST:	SLH

**SAMPLE ID: FR 998/35 Ceramic**

GEOMETRY USED FOR THIS TEST (A,B,or C):  
 DROP WEIGHT USED FOR THIS TEST (lbs):  
 INCREMENT OF HEIGHT(dh) TO BE EMPLOYED:  
 NUMBER OF SPECIMENS TO BE TESTED:

A
0.5
1
15

GEOM. (MAT-2229)  
TUP DIA. SUPPORT RING

Point	Station	Height	Angle	Distance	Remarks
A	625+00.4	3.00	0.01	1.00	Point A
B	625+00.4	1.25	+0.01	1.00	Point B
C	625+00.4	0.84	+0.01	1.00	Point C

Use "X" for failure. Use "O" for non-failure

[illegible]

**AVERAGE:**

Q:\XLD\CS\MATERIAL\DROP\PART.XLS  
REVISION DATE: 5-1-2000

ASHLAND SPECIALTY CHEMICAL CO.  
PHYSICAL TESTING LAB  
ASTM D-5420-98a  
(MAT-2229)

DROP DART ANALYSIS CONTINUED (page 2)

Total failures =  
 Total non-failures =  
 Events (N) =  
 Q =

1  
 2  
 3  
 4  
 5  
 6  
 7  
 8  
 9  
 10  
 11  
 12  
 13  
 14  
 15  
 16  
 17  
 18  
 19  
 20  
 21  
 22  
 23  
 24  
 25  
 26  
 27  
 28  
 29  
 30  
 31  
 32  
 33  
 34  
 35  
 36  
 37  
 38  
 39  
 40  
 41  
 42  
 43  
 44  
 45  
 46  
 47  
 48  
 49  
 50  
 51  
 52  
 53  
 54  
 55  
 56  
 57  
 58  
 59  
 60  
 61  
 62  
 63  
 64  
 65  
 66  
 67  
 68  
 69  
 70  
 71  
 72  
 73  
 74  
 75  
 76  
 77  
 78  
 79  
 80  
 81  
 82  
 83  
 84  
 85  
 86  
 87  
 88  
 89  
 90  
 91  
 92  
 93  
 94  
 95  
 96  
 97  
 98  
 99  
 100  
 101  
 102  
 103  
 104  
 105  
 106  
 107  
 108  
 109  
 110  
 111  
 112  
 113  
 114  
 115  
 116  
 117  
 118  
 119  
 120  
 121  
 122  
 123  
 124  
 125  
 126  
 127  
 128  
 129  
 130  
 131  
 132  
 133  
 134  
 135  
 136  
 137  
 138  
 139  
 140  
 141  
 142  
 143  
 144  
 145  
 146  
 147  
 148  
 149  
 150  
 151  
 152  
 153  
 154  
 155  
 156  
 157  
 158  
 159  
 160  
 161  
 162  
 163  
 164  
 165  
 166  
 167  
 168  
 169  
 170  
 171  
 172  
 173  
 174  
 175  
 176  
 177  
 178  
 179  
 180  
 181  
 182  
 183  
 184  
 185  
 186  
 187  
 188  
 189  
 190  
 191  
 192  
 193  
 194  
 195  
 196  
 197  
 198  
 199  
 200  
 201  
 202  
 203  
 204  
 205  
 206  
 207  
 208  
 209  
 210  
 211  
 212  
 213  
 214  
 215  
 216  
 217  
 218  
 219  
 220  
 221  
 222  
 223  
 224  
 225  
 226  
 227  
 228  
 229  
 230  
 231  
 232  
 233  
 234  
 235  
 236  
 237  
 238  
 239  
 240  
 241  
 242  
 243  
 244  
 245  
 246  
 247  
 248  
 249  
 250  
 251  
 252  
 253  
 254  
 255  
 256  
 257  
 258  
 259  
 260  
 261  
 262  
 263  
 264  
 265  
 266  
 267  
 268  
 269  
 270  
 271  
 272  
 273  
 274  
 275  
 276  
 277  
 278  
 279  
 280  
 281  
 282  
 283  
 284  
 285  
 286  
 287  
 288  
 289  
 290  
 291  
 292  
 293  
 294  
 295  
 296  
 297  
 298  
 299  
 300  
 301  
 302  
 303  
 304  
 305  
 306  
 307  
 308  
 309  
 310  
 311  
 312  
 313  
 314  
 315  
 316  
 317  
 318  
 319  
 320  
 321  
 322  
 323  
 324  
 325  
 326  
 327  
 328  
 329  
 330  
 331  
 332  
 333  
 334  
 335  
 336  
 337  
 338  
 339  
 340  
 341  
 342  
 343  
 344  
 345  
 346  
 347  
 348  
 349  
 350  
 351  
 352  
 353  
 354  
 355  
 356  
 357  
 358  
 359  
 360  
 361  
 362  
 363  
 364  
 365  
 366  
 367  
 368  
 369  
 370  
 371  
 372  
 373  
 374  
 375  
 376  
 377  
 378  
 379  
 380  
 381  
 382  
 383  
 384  
 385  
 386  
 387  
 388  
 389  
 390  
 391  
 392  
 393  
 394  
 395  
 396  
 397  
 398  
 399  
 400  
 401  
 402  
 403  
 404  
 405  
 406  
 407  
 408  
 409  
 410  
 411  
 412  
 413  
 414  
 415  
 416  
 417  
 418  
 419  
 420  
 421  
 422  
 423  
 424  
 425  
 426  
 427  
 428  
 429  
 430  
 431  
 432  
 433  
 434  
 435  
 436  
 437  
 438  
 439  
 440  
 441  
 442  
 443  
 444  
 445  
 446  
 447  
 448  
 449  
 450  
 451  
 452  
 453  
 454  
 455  
 456  
 457  
 458  
 459  
 460  
 461  
 462  
 463  
 464  
 465  
 466  
 467  
 468  
 469  
 470  
 471  
 472  
 473  
 474  
 475  
 476  
 477  
 478  
 479  
 480  
 481  
 482  
 483  
 484  
 485  
 486  
 487  
 488  
 489  
 490  
 491  
 492  
 493  
 494  
 495  
 496  
 497  
 498  
 499  
 500  
 501  
 502  
 503  
 504  
 505  
 506  
 507  
 508  
 509  
 510  
 511  
 512  
 513  
 514  
 515  
 516  
 517  
 518  
 519  
 520  
 521  
 522  
 523  
 524  
 525

**Coded Height (I):**

Number of failures "X" at each height:

Number of non-fallures "O" at each height:

**Number of "EVENTS" at each height:**

**Disregard These Two Numbers:**

Lowest height which an "EVENT" occurs: ho =

[illegible]

二 二  
A B

卷之四  
四

## RESULTS:

	English Units
MEAN FAILURE HEIGHT (h) units in inches =	9.500 inches
STD DEVIATION OF SAMPLE HEIGHT (s <sub>h</sub> ) =	0.973 inches
MEAN FAILURE ENERGY (MFE) =	4,750 in-lbf

SI Units	241.300 mm	24.707 mm	0.636 joules
----------	------------	-----------	--------------

ASHLAND SPECIALTY CHEMICAL CO.  
PHYSICAL TESTING LAB

IZOD IMPACT

ASTM D-256 (MAT-2246)

AF NUMBER: 50989  
REQUESTOR: Fowler  
DATE: 11/27/2002  
ANALYST: SLH  
RANGE(in-lbs): 50

SAMPLE	THICKNESS			THICKNESS		READING	
	NOTCHED	UNNOTCHED	(in)	NOTCHED	UNNOTCHED	(ft-lbs)	UNNOTCHED
FR 998/35 Control	6.97	13.00	0.101	0.115	0.70	1.49	
	6.53	15.90	0.099	0.114	0.65	1.81	
	9.41	14.15	0.092	0.121	0.87	1.71	
	9.03	12.82	0.114	0.119	1.03	1.50	
	7.54	18.40	0.118	0.098	0.89	1.80	
MEAN	(ft-lbs / in)	14.81					
STD. DEV.	(ft-lbs / in)	2.38					
MEAN	S(J/M)	790.84					
STD. DEV.	S(J/M)	126.82					

**ASHLAND SPECIALTY CHEMICAL CO.  
PHYSICAL TESTING LAB**

**IZOD IMPACT  
ASTM D-256 (MAT-2246)**

AF NUMBER: 50989  
REQUESTOR: Fowler  
DATE: 11/27/2002  
ANALYST: SLH  
RANGE(in-lbs): 50

SAMPLE				THICKNESS	THICKNESS	READING	READING
		NOTCHED	UNNOTCHED	(in)	(in)	(ft-lbs)	(ft-lbs)
FR 998/35	1	6.97	13.00	0.101	0.115	0.70	1.49
Control	2	6.53	15.90	0.099	0.114	0.65	1.81
	3	9.41	14.15	0.092	0.121	0.87	1.71
	4	9.03	12.62	0.114	0.119	1.03	1.50
	5	7.54	18.40	0.118	0.098	0.89	1.80
MEAN	(ft-lbs / in)	7.90	14.81				
STD. DEV.	(ft-lbs / in)	1.27	2.38				
MEAN	SI(J/M)	421.52	790.84				
STD. DEV.	SI(J/M)	67.61	126.82				

SAMPLE				THICKNESS	THICKNESS	READING	READING
		NOTCHED	UNNOTCHED	(in)	(in)	(ft-lbs)	(ft-lbs)
FR 998/35	1	8.26	14.87	0.126	0.112	1.04	1.67
Ceramic	2	7.71	13.86	0.117	0.128	0.90	1.77
	3	7.96	12.60	0.120	0.135	0.96	1.70
	4	7.75	16.13	0.131	0.118	1.01	1.90
	5	9.06	13.79	0.122	0.120	1.11	1.65
MEAN	(ft-lbs / in)	8.15	14.25				
STD. DEV.	(ft-lbs / in)	0.56	1.32				
MEAN	SI(J/M)	435.03	760.79				
STD. DEV.	SI(J/M)	29.68	70.66				

10

**Ashland Chemical**

Research &amp; Development

**ANALYTICAL**  
Services & Technology**Request for QA Analysis**

\*Requests cannot be logged until requester and project number are completed.\*

Date Submitted	November 26 <sup>th</sup> , 02
Requester/Phone Number	S. Fowler x 3926
Ashland Division/Location	CPD
Project Number	7032340
Project Name	
Manufacturer/Customer	

AF Number	50989
Date Registered	11-26-02
Registered By	ASN
Estimated Comp. Date	12-5-02
Primary Analyst	SCH
Refer to APP	

Date Results Needed: 12-6-02	Safe Handling Precautions: (include MSDS or warnings of known hazardous properties)
---------------------------------	---

Sample ID →	FR 998/35 Control		FR 998/35 Ceramic							
	VALUE		VALUE		VALUE		VALUE		VALUE	
List Analyses ↓ Required ↓	EXPTD	DETD	EXPTD	DETD	EXPTD	DETD	EXPTD	DETD	EXPTD	DETD
1. % ash		30.5		31.5						
2. % glass		30.5		31.5						
3. % filler		0.0		0.0						
4.										
5.										
6.										
7.										
8.										
9.										
10.										

Remarks: \$240.00      \$120 \* 2 = 240  
urgent

☐ Standard ☒ Urgent      Charges Authorized By: \_\_\_\_\_ Date: \_\_\_\_\_

 Analyzed by: [Signature]      Approved by: JDS      Date: 11-27-02

 Direct inquiries to (614) 790-3278 or (800) 545-8779.  
 Requests may be faxed to (614) 790-4294.

 Analytical Form #018  
 Revised 19-Aug-97  
 Reorder No. 2899

APR. 06 2005

Model	Color	Nov04-Dec03	Nov03-Dec02	Nov02-Dec01	Model Summary	Nov04-Dec03	Nov03-Dec02	Nov02-Dec01	Total	
MODEL	COLOR	Sum of TOT1-12	Sum of TOT13-24	Sum of TOT25-36	Model Summary	Nov04-Dec03	Nov03-Dec02	Nov02-Dec01	Total	
LFH20APD	10	0	0	0	LFH20APD Total	-	-	-	-	
	20	0	0	0	LFH20BPD Total	-	-	-	-	
	30	0	0	0	LFH20CPD Total	-	-	-	-	
	40	0	0	0	LFH20DPD Total	-	-	-	-	
	50	0	0	0	LFH2120A Total	1,139	2,159	1,746	5,041	
	80	0	0	0	LFH2120B Total	1,333	1,159	1,734	4,226	
LFH20APD Total		0	0	0	LFH2120D Total	697	586	484	1,767	
LFH20BPD	10	0	0	0	LFH2120E Total	1,458	3,855	2,124	7,437	
	20	0	0	0	LFH2120F Total	326	660	281	1,266	
	30	0	0	0	LFH2120G Total	8	-	4	12	
	40	0	0	0	LFH2120J Total	137	-	126	263	
	50	0	0	0	LFH2120K Total	706	443	394	1,543	
	60	0	0	0	LFH2120N Total	12	-	-	12	
LFH20BPD Total		0	0	0	LFH2120P Total	-	-	15	15	
LFH20CPD	10	0	0	0	LFH2120S Total	786	640	219	1,645	
	20	0	0	0	LFH2120U Total	83	124	36	243	
	30	0	0	0	LFH2122E Total	69	54	146	269	
	40	0	0	0	LFH2122Z Total	-	-	-	-	
	50	0	0	0	LFH2123A Total	50	-	-	50	
	80	0	0	0	LFH2124 Total	-	-	-	-	
LFH20CPD Total		0	0	0	LFH2124A Total	-	-	-	-	
LFH20DPD	10	0	0	0	LFH2124B Total	17	35	-	52	
	20	0	0	0	LFH2124E Total	9	6	-	15	
	30	0	0	0	LFH2124K Total	12	6	22	42	
	40	0	0	0	LFH2124S Total	46	-	-	46	
	50	0	0	0	LFH2126A Total	-	-	-	-	
	80	0	0	0	LFH2126B Total	-	-	-	-	
LFH20DPD Total		0	0	0	LFH2126D Total	-	-	-	-	
LFH2120A	11	257	385	355	LFH2126E Total	-	-	-	-	
	12	5	0	0	LFH2126K Total	1	-	-	1	
	22	588	1259	930	LFH2126S Total	-	-	-	-	
	32	132	194	180	LFH2127S Total	1,066	-	-	1,066	
	42	139	203	258	LFH212CS Total	-	1	1	2	
	51	8	0	0	LFH3710A Total	2,107	5,496	12,088	19,691	
	52	4	22	15	LFH3710B Total	28	3	52	83	
	62	6	13	8	LFH3711A Total	1,762	160	-	1,922	
	82	0	0	0	LFH3711B Total	-	-	-	-	
	LFH2120A Total		1139	2156	1746	LFH3712A Total	1,671	845	-	2,516
	12	18	0	0	LFH3713A Total	305	-	-	305	
	LFH2120B	21	877	1	0	LFH37APD Total	-	-	-	-
22		407	791	1303	LFH37BPD Total	-	-	-	-	
32		31	113	182	LFH3810A Total	120	222	44	386	
41		108	5	0	LFH3810B Total	3	-	2	5	
42		78	115	239	LFH3810E Total	31	53	305	389	
51		7	10	8	LFH3810S Total	1	-	5	8	
52		2	0	0	LFH3810T Total	-	51	-	51	
62		7	44	2	LFH381CS Total	-	-	-	-	
82		0	80	0	LFH3910A Total	1,882	1,907	1,752	5,341	
LFH2120B Total		1333	1159	1734	LFH3910B Total	40	310	48	398	
11		216	115	160	LFH3910E Total	2,904	3,285	2,908	9,075	
LFH2120D		12	10	0	0	LFH3910G Total	102	76	14	192
	21	298	286	206	LFH3910J Total	37	111	146	294	
	22	0	0	0	LFH3910S Total	57	106	53	216	
	31	49	0	0	LFH3910T Total	-	-	-	-	
	32	43	66	45	LFH3910U Total	29	3	46	78	
	42	81	115	73	LFH3916U Total	53	0	8	70	
	52	0	4	0	LFH3917E Total	7	-	-	7	
	62	0	0	0	LFH391CS Total	104	-	32	136	
	82	0	0	0	LFH4120B Total	625	521	767	1,913	
	LFH2120D Total		687	586	484	LFH4120D Total	121	107	173	401
	LFH2120E	12	343	965	454	LFH4120E Total	263	507	321	1,091
		22	807	1860	982	LFH4120F Total	225	273	191	699
32		115	388	280	LFH4120K Total	222	282	252	756	
42		146	580	362	LFH4120N Total	-	-	-	-	
51		18	0	0	LFH4120S Total	58	50	58	166	
52		20	80	25	LFH4121E Total	-	-	-	-	
62		8	4	11	LFH412CS Total	35	83	578	696	
82		0	0	0	LFH5100B Total	123	51	45	219	
LFH2120E Total		1458	3855	2124	LFH5100H Total	8	21	30	59	
LFH2120F		11	75	83	36	LFH5100S Total	18	20	11	47
		12	1	0	0	LFH510CS Total	-	-	-	-
		22	186	407	183	LFHSD1A Total	66	52	185	303
	32	42	97	59	LFHSD1C Total	28	21	154	203	
	42	16	0	0	LFHSD1E Total	40	163	36	239	
	52	3	7	2	LFHSDCA Total	18	82	68	148	
	62	2	5	1	Grand Total	20,845	24,557	27,702	73,104	
	82	0	61	0						
	LFH2120F Total		325	660	281	Classics ONLY	7,954	9,727	7,332	25,013
	LFH2120G	11	0	0	0	Percent of Total	38%	40%	28%	34%
		12	4	0	0					
		22	0	0	0					
32		0	0	4						
41		0	0	0						



Helmet only sales

	Year	Feb05-Mar04	Feb04-Mar03
Descrip	Item8	Unit	Unit
Traditional	LFH2020A	317	253
Traditional	LFH2020B	38	165
Traditional	LFH2020C	22	5
Traditional	LFH20APD	-	-
Traditional	LFH20BPD	-	-
Traditional	LFH20CPD	-	-
Traditional	LFH20DPD	-	-
<b>Traditional Total</b>		<b>377</b>	<b>423</b>
Classic	LFH2120A	1,820	2,334
Classic	LFH2120B	669	974
Classic	LFH2120D	1,132	525
Classic	LFH2120E	2,585	2,548
Classic	LFH2120F	531	622
Classic	LFH2120G	18	1
Classic	LFH2120J	30	177
Classic	LFH2120K	331	398
Classic	LFH2120N	30	-
Classic	LFH2120P	-	-
Classic	LFH2120S	1,163	598
Classic	LFH2120U	73	173
Classic	LFH2122E	50	84
Classic	LFH2122Z	-	-
Classic	LFH2123A	50	-
Classic	LFH2124	-	-
Classic	LFH2124A	-	21
Classic	LFH2124B	17	32
Classic	LFH2124E	5	39
Classic	LFH2124K	13	1
Classic	LFH2124S	54	-
Classic	LFH2126A	1	-
Classic	LFH2126B	-	-
Classic	LFH2126D	-	-
Classic	LFH2126E	1	7
Classic	LFH2126K	1	-
Classic	LFH2126S	-	-
Classic	LFH2127S	1,066	-
Classic	LFH212CS	1	1
<b>Classic Total</b>		<b>9,641</b>	<b>8,535</b>
Lion	LFH3710A	2,387	4,048
Lion	LFH3710B	80	30
Lion	LFH3711A	2,556	1,188
Lion	LFH3711B	-	-
Lion	LFH3712A	2,554	3,655
Lion	LFH3713A	319	82
Lion	LFH37APD	-	-
Lion	LFH37BPD	-	-
<b>Lion Total</b>		<b>7,896</b>	<b>9,003</b>
Modern	LFH3810A	203	271

Modern	LFH3810B	3	-
Modern	LFH3810E	26	61
Modern	LFH3810S	1	-
Modern	LFH3810T	12	51
Modern	LFH381CS	-	-
Modern	LFH3910A	1,384	1,832
Modern	LFH3910B	53	295
Modern	LFH3910E	2,681	3,109
Modern	LFH3910G	115	73
Modern	LFH3910J	9	68
Modern	LFH3910S	70	82
Modern	LFH3910T	-	-
Modern	LFH3910U	7	32
Modern	LFH3916U	52	10
Modern	LFH3917E	9	7
Modern	LFH391CS	6	2
<b>Modern Total</b>		<b>4,631</b>	<b>5,893</b>
Heritage	LFH4120B	167	526
Heritage	LFH4120D	103	181
Heritage	LFH4120E	245	550
Heritage	LFH4120F	258	251
Heritage	LFH4120K	78	223
Heritage	LFH4120N	-	1
Heritage	LFH4120S	39	82
Heritage	LFH4121E	1	-
Heritage	LFH412CS	91	84
<b>Heritage Total</b>		<b>982</b>	<b>1,898</b>
Rescue	LFH5100B	158	70
Rescue	LFH5100H	50	21
Rescue	LFH5100S	30	29
Rescue	LFH510CS	6	-
Rescue	LFHSD1A	64	46
Rescue	LFHSD1C	28	21
Rescue	LFHSD1E	50	163
Rescue	LFHSDCA	142	50
<b>Rescue Total</b>		<b>528</b>	<b>400</b>
<b>Grand Total</b>		<b>24,055</b>	<b>26,152</b>

